



Mobile Generators

G 25 (T4i) **G 50 (T4i)** **G 70 (T3)**

Heavy-duty mobile generator for reliable power

The perfect range of machines to meet market and job site needs. These compact, sound-attenuated generators provide single and three-phase power for construction, commercial, industrial and special event applications providing continuous operating data on an easy to read LCD display. Skid-mounted units feature a fully integrated, large capacity fuel tank for long run times, even without a trailer.

Features:

- Ideally suited for construction sites where durability, reliability and flexibility are required to supply continuous power for applications such as lighting, cranes, concrete mixers and conveyor belts.
- Brushless, over-sized alternators with separate excitation winding and AVR (Automatic Voltage Regulation) provide superior motor starting and enhanced ability to run non-linear loads.
- Single switch start and simple, uncluttered control panel provide unmatched ease of use.
- Automatic remote start capability standard, ideal for temporary standby applications.
- Durable features like stainless steel external hardware and automotive corrosion treatment of select body parts provide a long-lasting, quality appearance ensuring a high resale value.
- Generator control panel swings open as one complete unit for easy serviceability.
- Factory-installed customized options are available. These include, but are not limited to, a fluid containment system, a cold weather options, a camlock panel etc.



Highway 18 East, Oxbow, SK S0C 2B0

Call (844) 732 9466

www.axiomequipmentgroup.com

Mobile Generator

G 25 G 50 G 70

TECHNICAL DATA		G 25	G 50	G 70
Length x width x height (skid mounted)	in (mm)	76.6 x 35 x 44.5 (1,946 x 889 x 1,130)	96.25 x 38 x 53 (2,445 x 965 x 1,346)	96.25 x 38 x 53 (2,445 x 965 x 1,346)
Length x width x height (with trailer)	in (mm)	133 x 60 x 69 (3,378 x 1,524 x 1,753)	160 x 67.5 x 80 (4,064 x 1,715 x 2,032)	60 x 67.5 x 80 (4,064 x 1,715 x 2,032)
Operating weight (skid mounted)	lb (kg)	2,332 (1,057)	3,783 (1,716)	4,069 (1,845)
Dry/shipping weight (skid mounted)	lb (kg)	1,911 (867)	3,178 (1,441)	3,464 (1,571)
Operating weight (with trailer)	lb (kg)	2,802 (1,271)	4,663 (2,115)	4,949 (2,244)
Prime output	kW/kVA	19.5/24.4	38/48	58/72
Standby output	kW/kVA	20.4/25.5	42/53	63/79
AC voltage (switchable)	V at 1~/V at 3~	120, 139, 240 / 208, 240, 460, 480		
Frequency	Hz	60	60	60
Power Factor	1~/3~	1.0/0.8	1.0/0.8	1.0/0.8
Voltage regulation, no load to full load	%	±1	±1	±1
Voltage regulation, steady state	%	±0.2	±0.2	±0.2
Generator insulation	class	H	H	H
Sound level at maximum load	dB(A) at 23 ft	65	67.2	68
Engine type		Tier 4i Isuzu	Tier 4i John Deere	Tier 3 John Deere
Operating speed	rpm	1,800	1,800	1,800
Rated standby power at rated speed	hp (kW) rpm	35.4 (26.4) 1,800	74 (55) 1,800	99 (74) 1,800
Power rating specification		SAE J1995, ISO 8528-1		
Displacement	in ³ (l)	133 (2.2)	275 (4.5)	275 (4.5)
Fuel tank capacity	gal (l)	58.4 (221)	84 (318)	84 (318)
Fuel consumption (at continuous load)	gal (l)/h	1.8 (6.8)	3.4 (12.9)	4.9 (18.7)
Battery		12V/750 CCA	12V/750 CCA	12V/750 CCA
Trailer hitch type		trailer specific	3-inch Pintle	3-inch Pintle
AC receptacles (1 ~ 120V - 20 amp GFI duplex)		2	2	2
AC receptacles (1 ~ 120/240V - 50 amp twist lock)		2	3	3

Standard Package - G 25, G 50, G 70

Package includes operator's manual and parts book. (Generator trailers and generator units sold separately.)

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Saskarc is an accredited Wacker Neuson equipment Dealer. Please consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Model Guide: G = Mobile Generator, 25-70 = Prime output in kVA; MGT = Mobile generator trailer



Highway 18 East, Oxbow, SK S0C 2B0

Call (844) 732 9466

www.axiomequipmentgroup.com